GHXV.EX27313 - PROPORTIONERS, FOAM CONCENTRATE

Proportioners, Foam Concentrate

See General Information for Proportioners, Foam Concentrate

FLUID EQUIPMENT INT. BVBA

RUMBEEKSEGRAVIER 166 UNIT D/E

8800 ROESELARE, BELGIUM

BLADDER TANK AND RATIO-FLOW CONTROLLER INVESTIGATED TO UL 162

53 to 3963 gal capacity ASME for vertical and horizontal installation

Following are equivalent length valves for the controllers (Models FFP) based on a roughness factor of 130 and schedule 40 steel pipes.

Controller Size In.	Equivalent Length Ft
FFP2	22.0
FFP3	17.5
FFP4	29.3
FFP6	24.9
FFP8	23.0

Refer to the individual foam concentrate Listings for operating limitations with specific combinations of foam concentrates and proportioners.

Trademark and/or Tradename:

Last Updated on 2018-10-11

EX27313

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

>_____ Accept

. Learn More